

INCINER8

Waste Incineration Model P25 M1

Waste Incinerators

The P25 is designed to burn Type IV pathological waste and infectious and contaminated "red bag," surgical dressings, plastic test devices and other wastes. If you are paying a high fee to haul these waste materials to a disposal site, ***now is the time to consider the on-site Incineration alternative.***



Model P25 M1



Benefits

Fast, complete, efficient waste disposal

- Heavy duty ceramic grates allow burning from below.
- Concave refractory bottom acts as a hearth for waste that falls through grate openings.
- Insulated and refractory lined secondary chamber with exit temperatures of up to 1000 deg C and one (1) second retention with model M1.

Minimum installation and start up time

- Factory assembled, aluminized steel jacket lined with refractory and firebrick.
- Monitors, recorders and other accessory equipment available.

Easy and safe operation

- Large counter-balanced fill door with electrical lockout.
- Automatic control system provides preset burn times and shut off.
- Reload light indicates to operator when it is time to recharge.
- be required for burnout of final charge.

Low energy consumption levels

- Programmable digital temperature controls maintain temperature, assuring complete combustion while conserving fuel.
- Pressure blower with modulating air control creates turbulence and distributes combustion air to secondary chamber.
- Secondary burner with temperature activated modulating control provides fast preheat and sustains high temperature performance at low energy consumption levels.

Charging rate

Up to 600kgs per ten-hour day of Type IV pathological waste or red bag waste rated at 2200 BTU's per kg. Based on batch loading twice daily.



On-site cremation is a thorough, fast, and cost effective way to dispose of carcasses. Inciner8's P25 incinerator system destroys pathogens. Our various models are engineered to meet strict air emission regulations without offensive smoke or odour. The P25-M1 provides a one (1) second retention of emissions in the secondary burn



Technical Specifications	Model P25	Model P25 M1
Fuel	Oil or Gas	Oil or Gas
Capacity (Cubic Mtr)	0.65	0.65
Ave Capacity	60 kg per hour	60 kg per hour
Fuel Consumption (ltrs / hr)	13	20
External Dimensions		
Length (mm)	2300	2600
Width (mm)	1220	1500
Height Incl. Flue (mm)	7000	7700
Door Opening (mm)	610 x 710	610 x 710
Internal Dimensions		
Length (mm)	1524	1524
Width (mm)	620	620
Height (mm)	720	720
Operation		
Min. Operating Temperature	950	950
Max. Operating Temperature	1320	1320
Residency Time in Second Chamber	.5 sec	1 sec
Temperature Monitoring	YES	YES



Dealer Stamp

INCINER8

Shakespeare Hse. 37-39 Shakespeare Street, Southport PR8 5AB, England
 Tel +44 (0) 1704 548508
 Fax +44 (0) 1704542461
 Email : info@inciner8.com
 Web : www.inciner8.com